



“ For over a decade Coolspirit have been supplying the UK’s top organisations with storage products and solutions so be assured we will meet your requirements head on.

It’s all about getting things right first time, quickly and simply! ”

Damon Robertson
Coolspirit Ltd

Our address

24 The Bridge Business Centre
Beresford Way
Chesterfield
S41 9FG

Get in touch

Call us on: 01246 454222
Email us: web@coolspirit.co.uk
Find us: [View location map](#)
Web: www.coolspirit.co.uk

Office hours

mon - thurs 8:30am - 5:30pm
fri 8:30am - 5pm
sat - sun Closed

“ Boost your storage buying power...
use ours! ”

Buy with confidence from
Coolspirit your authorised
Dot Hill Partner






AssuredSAN™

3420 and 3430 Data Protection Solutions

BENEFITS



Assured Data Protection

AssuredSnap™ - 1000 snapshots
AssuredCopy™ - 512 volume copies

Scalable Performance

Dual RAID controller
Data rates up to 10Gb/sec. iSCSI
up to 7 expansion units per system
support for SAS, SATA, solid state drives
max 144 drives - 3420, 96 - 3430

Built in Redundancy

RAID 0, 1, 3, 5, 6, 10, 50
Redundant, hot swap components
Built-in schedule capability

Green Features

EcoStor™ Economically and environmentally sound technologies

- SimulCache™ - Low latency cache mirroring
- Battery-free cache backup
 - DC power option
 - Drive-spin-down

RoHS-6 and WEEE compliant

Rugged Chassis

NEBS Level 3 Compliant
MIL STD 810F Compliant (Storage Requirements)
European Telco Compliant

INTEGRATED DATA PROTECTION

Dot Hill's AssuredSAN™ Solutions offer an innovative and comprehensive view of storage management – Store, Back up and Restore instantly. The AssuredSAN™ Solutions combine high performance and high capacity storage with the ease of the RAIDar™ management GUI which provides a complete set of features and tools to ensure that storage administration is the easiest job in the datacenter.

Today's solutions should not only store data, but ensure that it can be restored in an instant. That is where the AssuredSAN™ 3420S and 3430S come in – their 10Gb iSCSI hosts can double throughput, providing power to support your most demanding applications, along with optimal levels of data protection. With Dot Hill's solutions you have the assurance that you can store, instantly back up, and instantly restore from that spot. And you don't have to be a storage expert to make it work.

These next generation iSCSI storage arrays are ideal for small to medium sized organizations that are experiencing growing bandwidth demands, driven by network convergence and I/O port consolidation trends. The AssuredSAN™ 3420 and 3430 SAN storage systems are designed to scale with your networking environment, providing greater data access speed for distributed computing, virtual server, and other demanding applications.

Future Growth

As you plan future storage networking products, these 10Gb iSCSI arrays give you solid options for both today and tomorrow. With AssuredSAN arrays you immediately gain greater processing power, reduced energy consumption, and data protection features through an intuitive GUI interface.

Key Applications

- Virtualized Storage for virtual server environments
- Business Critical application – email, databases, OLTP
- IP-based video surveillance systems/CCTV/Video ISR
- Video streaming, editing, video-on-demand, high definition imaging
- High performance computing - such as geospatial



Complete Data Protection Included

The AssuredSAN 3420S and 3430S Fibre Channel Arrays come fully licensed with 1000 AssuredSnaps and 256 AssuredCopies – providing necessary protection for business critical applications such as email. AssuredSnap instantly takes volume snapshots, creating point-in-time backups that can be used to instantly restore your data after a system failure. In addition, you get AssuredCopy, which protects against disk failures.

Environmentally Responsible

Utilizing Dot Hill's patented EcoStor™ technology, these systems have completely eliminated cache batteries, using instead super capacitors and flash memory to provide infinite cache backup during a power loss, while being environmentally friendly. The AssuredSAN 3000 Series also features energy saving drive-spindown. With the addition of drive spin-down, mixed drive type support and dual protocol interfaces, users can now combine both high performance primary volumes and secondary storage with different performance and energy usage profiles in the same physical unit.

Enhanced Performance

The storage systems leverage patented SimulCache™ technology that instantly and simultaneously mirrors cache between RAID controllers, leading to significant performance improvements over traditional implementations.

AssuredCopy™ and AssuredSnap™

The AssuredSAN data protection and disaster recovery solution comes fully licensed with both AssuredSnap™ and AssuredCopy™ data protection software. With up to 1000 snapshots capability, AssuredSANs offer necessary protection for business critical applications such as email, databases, and file sharing.

AssuredSnap instantly takes volume snapshots, creating point-in-time backups that can be used to instantly restore your data after a system failure. In addition, you get AssuredCopy, which protects against disk failures.

Storage Made Easy

AssuredSAN arrays are easy to configure and manage with RAIDar 2.0, our intuitive web based interface which provides storage setup and monitoring without the need for host based software. RAIDar 2.0 saves time with configuration and installation wizards, and schedulers for snapshots and replication.

- Easy to set up Configuration, Installation Wizards

models

Without Software - 3420C, 3430C

The AssuredSAN 3420C and 3430C are hardware only models that ship with the storage array, drives, rail kit, cables, Installation Guide, and Bronze support. The Try and Buy menu in the RAIDar management interface allows customers to start using data protection or remote replication software at any time.

With 2.5-inch drives

Drives per array	up to 24
Max capacity per chassis	14.4TB

PHYSICAL

Depth (excluding cables)	21.3 Inches / 54.0 cm
Height	3.5 Inches / 8.9 cm
Width	17.6 Inches / 44.7cm
Chassis weight	44 lbs / 20kg
w/146GB drives	60 lbs / 27.2kg

- Automated 'Set and Forget' scheduler for snapshots
- Instant Backup AssuredSnap instantly takes point in time copies
- Replication AssuredRemote quickly transmits changes to your remote site
- Instant Restore No time consuming tape recoveries. Use our snapshots to step back in time.

support

Warranty

AssuredSANs come with a three year standard hardware warranty, a 90 day software warranty, and Bronze level support, which provides you with expert 24X7 technical telephone support, access to our SANsolve and the Customer Resource Center with knowledge base articles, product documentation and firmware upgrades.

Gold and Platinum Support Programs

Dot Hill is equipped to provide the extra level of support you may need to meet your service level agreements. Our Gold and Platinum levels of support are designed to offer maximum responsiveness anywhere in the world. These programs include options for same day advance shipment, parts depot access, next business day and 4-hour onsite service. We also offer extended hardware warranties and extended software support packages.

Professional Services

In addition, Dot Hill offers professional services such as installation, remote monitoring, and remote site DR set up, and configuration, designed to make it simple and straightforward to fully deploy AssuredSAN storage solutions.

shipping information

3420C, 39S0S

Packaged product weight 67.5 lbs with drives
 Packaged product dimensions Width 25.5", Height 10", Depth 28.5"

3430C, 3430S

Packaged product weight 85.5 lbs with drives
 Packaged product dimensions Width 25.5", Height 10", Depth 28.5"

With Software - 3420S, 3430S

The AssuredSAN 3420R and 3430R are hardware and software bundles which ship with a storage array and drives, AssuredRemote, 1000 Assured-Snap instances, 512 AssuredCopy instances, rail kit, cables, installation guide, and Bronze support.

With 3.5-inch drives

Drives per array	up to 12
Max capacity per chassis	24TB

PHYSICAL

Depth (excluding cables)	23.7 Inches / 60.2 cm
Height	3.5 Inches / 8.9 cm
Width	17.6 Inches / 44.7 cm
Chassis weight	44lbs. / 20kg
w/500GB drives	68lbs. / 30.84kg



GENERAL

Host speed	10Gb iSCSI
IOPs	264,000
Data protection	AssuredSnap™, AssuredCopy™,

EXPANSION

Max number of chassis	up to 8 (1 RAID, 7 JBOD)
Expansion units	Dot Hill 3120, 3130

PROTOCOLS AND STANDARDS

ICMP (RFC 792, 950, 1256)	TCP (RFC 793)
IP (RFC, 894, 1092)	SCSI-2 and SCSI-3

HOSTS

Initiators	10Gb NIC or 10Gb iSCSI
Interface Type	SFP+
External Ports	2/4 10Gb iSCSI (Single/Dual Controller)

DRIVE SUPPORT

3420	3Gb or 6Gb SAS - 146GB or 300GB 10K
	3Gb or 6Gb SAs - 72GB or 146GB 15K
	6Gb SAS - 500GB 7K
	3Gb SATA SSD - 32GB SLC, 64GB SLC, 80GB MLC

3430	6Gb SAS - 300GB, 450GB or 600GB 15K
	SATA II - 500 GB, 750GB, 1TB 7K, 1TB or 2GB 5K
	3Gb SATA SSD - 32GB SLC, 64GB SLC, 80GB MLC

RAID

Levels Supported	0, 1, 3, 5, 6, 10 and 50
RAID Type	Hardware
Cache Memory	2GB per controller
Cache Backup	Battery-free protection w/super capacitors
Virtual disks per System	32
Volumes per virtual disk	256
Volumes per System	256
Mirrored Cache	Yes - SimulCache™
Super Capacitor Cache Backup	Yes
Cache Backup to Flash	Yes - Non-volatile

MANAGEMENT

Interface Types	10/100 Ethernet, Mini USB
Protocols Supported	SNMP, SSL, SSH, SMTP, SMI-S Provider, HTTP(S)
Management Consoles	WEB GUI, CLI
Management Software	RAIDar 2.0

POWER REQUIREMENTS - AC INPUT

Input Power Requirements	100-240VAC 50/60Hz
Max Input Power	436W max maximum continuous
Heat Dissipation	1488 BTUs/hour

Bronze Rated - high efficiency

82% @ 20% load
86% @ 80% load
85% @ 100% load

TEMPERATURE AND HUMIDITY RANGES

Operating Temperature	41 °F to 104 °F (5 °C to 40 °C)
Shipping Temperature	-40 °F to 158 °F (-40 °C to 70 °C)
	Note: Derate 2 °C for every km, up to 3000 meters
Operating Humidity	10% to 90% RH @ 104 °F (40 °C), non-condensing
Non-Operating Humidity	Up to 93% RH @ 104 °F (40 °C) non-condensing

DECLARED ACOUSTIC NOISE LEVELS

Sound Power	LWAd=6,75 B
Sound Pressure	LpAm - 55dB _A

SHOCK AND VIBRATION

Shock, Operational	10G's for 10 ms (3720) 5G's for 10 ms (3730)
Shock, Non-Operational	15G 11ms, half sine
Vibration, Operational	5Hz to 500Hz, 0.21Grms flat spectrum

Vibration, Non-Operational	3-365-3Hz, 1.22 Grms, z-axis, 0.85 Grms, X&Y axis shaped spectrum
----------------------------	-------------------------------------------------------------------

HIGH-AVAILABILITY FEATURES

Redundant Hot-Swap Controllers	Yes
Redundant Hot-Swap Disk, Fans, Power	Yes
Dual Power Cords	Yes
Hot Standby Spare	Yes
Automatic Failover	Yes
Multi-Path Support	Yes
Snapshot with AssuredSnap™	Yes
Volume Copy with AssuredCopy™	Yes
Remote Replication with AssuredRemote™	Yes

REGULATORY

Safety	UL 60950-1, 1st edition, 2007-10-31 (USA)
	CAN/CSA-C22.2 No.60950-1-03, 1st Edition, 2006-7 (Canada)
	EN 60950-1:2006 (European Union)
	EC 60950-1:2001 (International)
	EN 60950-1:2001 +A11:2004 (GS Mark, Germany)
	CCC Mark (power supply only, China PRC)

Electromagnetic Compatibility

<i>Emissions</i>	CFR 47 Part 15 Subpart B Class A (U.S.A.)
	ICES-003:2004 Class A (Canada)
	EN 55022:2006 +A1:2007 Class A (EU)
	EN 300 386 V1.4.1:2008 Class A (EU Telco)
	AS/NZS CISPR 22:2009 Class A (Australia, New Zealand)
	VCCI:2009-04 Class A (Japan)
	GOST R 51318.22-99 Class A (Russia)
	KN 22 Class A (S. Korea)
	CNS 13438:2006 Class A (Taiwan)

Harmonics

<i>Flicker</i>	EN 61000-3-3:1995 +A1:2001+A2:2005 (EU)
----------------	-----------------------------------------

Immunity

	EN 55024:1998 +A1:2001+A2:2003 (EU)
	EN 300 386 V1.4.1:2008 (EU Telco)
	GOST R 51318.24-99 (Russia)
	KN 24 (S. Korea)

RoHS and WEEE	RoHS-6/6 Compliance, China RoHS, WEEE
---------------	---------------------------------------

Country Approvals	United States, Canada, European Union (EU), Australia/New Zealand, Japan, China (PRC), Russia, Mexico, South Africa, Germany, South Korea, Taiwan
-------------------	---------------------------------------------------------------------------------------------------------------------------------------------------

SUPPORT

Software Warranty	90 days
Standard Hardware Warranty	3 years
Environmental Monitoring	SNMP, CLI, RAIDar 2.0, SMTP, SMI-S Provider
SMTP	Yes
Remote Diagnostics	Yes
Non-disruptive Updates	Yes
Non-disruptive Volume Expansion	Yes for primary volumes and snapshot volumes and snapshots

